

# UNITED GX PLUS

## Product Description

Synthetic Passenger Car Motor Oil (PCMO) that delivers the enhanced performance of lubricating oil technology to maximize protection for the latest gasoline fueled engines. It meets the performance level of API SQ and exceeds the most demanding requirements of modern engine's emission control and oil consumption standards. In today's energy conscious era, this oil is also formulated to improve fuel efficiency for consumers.

## Applications / Benefits

- \* Exceeds the highest U.S Lubricating oils standards for gasoline and LPG/CNG engines
- \* Silky smooth operation for all high performance engines
- \* Increases emission system durability and improves fuel efficiency
- \* Improves piston cleanliness and increases engine sludge protection

## Typical Characteristics

| Test Description            | Method      | Unit    |             |             |              |
|-----------------------------|-------------|---------|-------------|-------------|--------------|
| SAE Viscosity Grade         | SAE J 300   | -       | <b>5W30</b> | <b>5W40</b> | <b>10W40</b> |
| Density @ 15 °C             | ASTM D 4052 | kg/L    | 0.858       | 0.860       | 0.863        |
| Flash Point                 | ASTM D 92   | °C      | 220         | 218         | 228          |
| Pour Point                  | ASTM D 97   | °C      | -36         | -36         | -36          |
| Kinematic Viscosity @ 40°C  | ASTM D 445  | cSt     | 67.2        | 90.0        | 97.7         |
| Kinematic Viscosity @ 100°C | ASTM D 445  | cSt     | 11.4        | 14.5        | 14.7         |
| Viscosity Index             | ASTM D 2270 | -       | 163         | 168         | 156          |
| TBN                         | ASTM D 2896 | mgKOH/g | 7.2         | 7.2         | 7.2          |

## Specifications, Approvals & Recommendations

- |         |                           |
|---------|---------------------------|
| * API   | SQ-RC                     |
| * ILSAC | GF-7A IN SAE 5W30         |
| * FORD  | WSS-M2C961-A1 IN SAE 5W30 |

Reference No.  
5157G23SQGF7REV1  
CT0045

Last revised date:  
9/9/2026