United Oil
PERFORMANCE • VALUE • RELIABILITY

A member of Repsol Group
REPSOL

UNITED SUPER RACING 4T

Product Description

Hydrotreated motorcycle oil is a multigrade lubricant designed for four-stroke motorcycle engines. It contains a balanced blend of select high performance, high viscosity index base stocks and a special proprietary additive package. This motorcycle oil is engineered to provide unsurpassed wear protection, engine cleanliness and oxidation resistance, as well as consistent viscosity.

This is a powerful detergent type of motor oil. It can be used in most 4T engines including Yamaha, Honda, Kawasaki, Suzuki, and Kubota.

Applications / Benefits

* Reduces engine wear and extends engine life
* Protects engine under severe operating conditions
* Retards harmful deposit formation on vital engine parts
* Protects against rust and corrosion

Typical Characteristics

Test Description	Method	Unit				
SAE Viscosity Grade	SAE J 300	-	**10W30**	**10W40**	**15W40**	**15W50**
Density @ 15 °C	ASTM D 4052	kg/L	0.865	0.865	0.867	0.877
Flash Point	ASTM D 92	°C	216	218	220	220
Pour Point	ASTM D 97	°C	-30	-30	-27	-27
Kinematic Viscosity @ 40°C	ASTM D 445	cSt	76.7	100.9	112.9	155.7
Kinematic Viscosity @ 100°C	ASTM D 445	cSt	11.8	14.8	14.7	19.8
Viscosity Index	ASTM D 2270	-	148	153	134	146
TBN	ASTM D 2896	mgKOH/g	6	6	6	6

ISSUED BY UNITED OIL COMPANY PTE. LTD. TEL: (65) 6861 1157 FAX: (65) 6861 3101

Furnishing the information contained herein does not constitute a representation by United that any product or process is free from patent infringement claims of any third party nor does it constitute the granting of a license under any patent of United or any third party. United assumes no liability for any infringement which might arise out of product. The information and suggestions for use and application presented herein represent the best information available to us and believed to be reliable. They should not, however, be construed as controlling suggestions, and users urged to conduct confirmatory test to determine final suitability for their specific end uses. United warranty only that its product meet the specifications which it sets for them and specifically DISCLAIMS ALL OTHER WARRANTS relating to the products and the application thereof. EXPRESS or IMPLIED including but not limited to warrants of MERCHANTABILITY and FITNESS.

United Oil
PERFORMANCE • VALUE • RELIABILITY

A member of Repsol Group
REPSOL

Typical Characteristics

Test Description	Method	Unit	
SAE Viscosity Grade	SAE J 300	-	**20W50**
Density @ 15 °C	ASTM D 4052	kg/L	0.878
Flash Point	ASTM D 92	°C	248
Pour Point	ASTM D 97	°C	-18
Kinematic Viscosity @ 40°C	ASTM D 445	cSt	183.2
Kinematic Viscosity @ 100°C	ASTM D 445	cSt	20.0
Viscosity Index	ASTM D 2270	-	127
TBN	ASTM D 2896	mgKOH/g	6

Suggested For The Following Uses

*	API	SL
*	JASO	MA2

Reference No.
6128G2SLMA24TREV2

Last revised date:
02/05/2025

ISSUED BY UNITED OIL COMPANY PTE. LTD. TEL: (65) 6861 1157 FAX: (65) 6861 3101

Furnishing the information contained herein does not constitute a representation by United that any product or process is free from patent infringement claims of any third party nor does it constitute the granting of a license under any patent of United or any third party. United assumes no liability for any infringement which might arise out of product. The information and suggestions for use and application presented herein represent the best information available to us and believed to be reliable. They should not, however, be construed as controlling suggestions, and users urged to conduct confirmatory test to determine final suitability for their specific end uses. United warranty only that its product meet the specifications which it sets for them and specifically DISCLAIMS ALL OTHER WARRANTS relating to the products and the application thereof. EXPRESS or IMPLIED including but not limited to warrants of MERCHANTABILITY and FITNESS.