

# UNITED ATF LT

## Product Description

Automatic transmission fluid formulated with selected high viscosity index synthetic base stocks and latest additive technology available allowing very high performance needed for the demanding requirements of passenger cars automatic gearboxes. It can be used in a broad range of automatic transmission standards and provides excellent service in a wide variety of North American, European, and Asian vehicles. It's particularly suitable for 4 and 5 speeds automatic transmissions.

This oil is recommended for use in all GM vehicles DII, DIII(G), DIII(H). It exceeds the published JASO 1A, Ford M and Allison C-4 fluid specifications and suitable for use in automatic transmission recommending Toyota Type T-IV.

## Applications / Benefits

- \* Provides excellent oxidation and thermal stability for longer life.
- \* Superior wear protection to protect critical transmission components.
- \* Excellent viscosity stability(high VI), application in a wide variety of Auto Transmission.
- \* Much enhanced fluidity at very low temperature service.

## Typical Characteristics

Test Description	Method	Unit	
Density @ 15 °C	ASTM D 4052	kg/L	0.8530
Flash Point	ASTM D 92	°C	198
Pour Point	ASTM D 97	°C	-45
Kinematic Viscosity @ 40°C	ASTM D 445	cSt	38.1
Kinematic Viscosity @ 100°C	ASTM D 445	cSt	7.24
Viscosity Index	ASTM D 2270	-	157

## Suitable For Use

\* ESSO LT 71141

Reference No.  
4801G23REV0

Last revised date:  
1/6/2023