

UNITED ATF SP-IV

Product Description

Fully Synthetic Automatic Transmission Oil specially formulated with high performance fully synthetic base oils and advanced additive technology specifically to provide optimum performance and protection for the automatic transmissions requirements for the ATF SP-IV specification that is the most common ATF used for Hyundai and Kia vehicles automatic transmissions.

This product optimized friction properties provides smooth and comfortable gear shifting and prevents transmission vibration. Excellent thermal and oxidation stability keeps transmission clean to help provide outstanding performance even under severe driving conditions and extend fluid life. Ultra low-temperature fluidity helps to provide immediate protection at starting in cold weather and consume less fuel.

Applications / Benefits

- * Provides excellent oxidation and thermal stability for longer life
- * Superior wear protection to protect critical transmission components
- * Protection against corrosion and foaming
- * Outstanding low-temperature fluidity

Typical Characteristics

Test Description	Method	Unit	
Density @ 15 °C	ASTM D 4052	kg/L	0.845
Flash Point	ASTM D 92	°C	198
Pour Point	ASTM D 97	°C	-45
Kinematic Viscosity @ 40°C	ASTM D 445	cSt	26.7
Kinematic Viscosity @ 100°C	ASTM D 445	cSt	5.7
Viscosity Index	ASTM D 2270	-	160
Appearance	Visual	-	Red

Specifications, Approvals & Recommendations

- | | |
|-----------|-----------|
| * HYUNDAI | ATF SP-IV |
| * KIA | ATF SP-IV |

Reference No.
5392G3ATFSPIVREV1

Last revised date:
13/10/2026