

UNITED ATF WS

Product Description

Fully Synthetic ATF WS formulated with selected synthetic base stocks and latest additive technology available that provides excellent service in applications calling for low viscosity ATF, such as: Toyota Type WS.

Synthetic base stocks and stability of United ATF WS protects against thermal breakdown at high operating temperatures, while still providing outstanding performance at ambient temperatures as low as -45° C. Moreover, it improves overall transmission durability and cleanliness.

Applications / Benefits

- * Provides excellent oxidation and thermal stability for longer life
- * Outstanding rust and corrosion protection
- * Superior wear protection to protect critical transmission components
- * Much enhanced fluidity at very low temperature

Typical Characteristics

Test Description	Method	Unit	
Density @ 15 °C	ASTM D 4052	kg/L	0.845
Flash Point	ASTM D 92	°C	198
Pour Point	ASTM D 97	°C	-45
Kinematic Viscosity @ 40°C	ASTM D 445	cSt	26.7
Kinematic Viscosity @ 100°C	ASTM D 445	cSt	5.7
Viscosity Index	ASTM D 2270	-	160
Appearance	-	-	Red

Specifications, Approvals & Recommendations

* TOYOTA / LEXUS / SCION TYPE WS

Reference No.
5292G3ATFWSREV0

Last revised date:
29/8/2025