

UNITED MTB SCOOTER 4T API SL

Product Description

Hydrotreated, high performance four-stroke motorcycle oil that is specially designed for modern scooter engines with automatic transmissions and dry clutch. As the scooter engines are compact and enclosed, they operate at higher temperatures and hence need specially designed oils since common motorcycle oils may not provide adequate protection. It contains a balanced blend of select high performance, high viscosity index hydro-treated base stocks and a special proprietary additive package to ensure smoother rides even in severe city stop & go driving conditions. The friction modifier used in this oil reduces engine friction leading to improved fuel economy.

This product is a multigrade lubricant designed for four-stroke motorcycle engines. It meets the requirements of the API SL and JASO MB for four-stroke engine oils. It can be used in most 4T JASO MB engines including Yamaha, Honda, Kawasaki, Suzuki, and Kubota.

Applications / Benefits

- * Reduces engine wear and extends engine life
- * Low friction formula of the oil ensures smoother ride
- * Potential to provide fuel economy benefit
- * Better thermo-oxidative stability even at higher temperatures

Typical Characteristics

Test Description	Method	Unit		
SAE Viscosity Grade	SAE J 300	-	10W30	10W40
Density @ 15 °C	ASTM D 4052	kg/L	0.862	0.864
Flash Point	ASTM D 92	°C	212	216
Pour Point	ASTM D 97	°C	-30	-30
Kinematic Viscosity @ 40°C	ASTM D 445	cSt	78.1	102
Kinematic Viscosity @ 100°C	ASTM D 445	cSt	11.8	14.9
Viscosity Index	ASTM D 2270	-	145	152
TBN	ASTM D 2896	mgKOH/g	6.1	6.1

Specifications, Approvals & Recommendations

* API	SL
* JASO	MB

Reference No.
4117G2SLMB4TREV0

Last revised date:
20/3/2024