

UNITED XTG-Q

Product Description

Gasoline engine oil formulated with selected base fluids and technologically advanced additive to deliver outstanding engine performance and protection for today's gasoline engine powered cars and trucks. It meets the performance requirement of API SQ specification with enhanced properties in the areas of piston cleanliness, wear protection, fuel efficiency and prolong engine life.

Applications / Benefits

- * Silky smooth operation for all high-performance engines.
- * Increases emission system durability and improves fuel efficiency.
- * Improves piston cleanliness and sludge control.
- * Excellent anti-wear properties and extends service life.

Typical Characteristics

Test Description	Method	Unit	10W30	10W40	15W40	20W50
SAE Viscosity Grade	SAE J 300	-				
Density @ 15 °C	ASTM D 4052	kg/L	0.868	0.868	0.873	0.879
Flash Point	ASTM D 92	°C	218	220	224	244
Pour Point	ASTM D 97	°C	-30	-30	-27	-18
Kinematic Viscosity @ 40°C	ASTM D 445	cSt	73.8	101.2	110.0	179.0
Kinematic Viscosity @ 100°C	ASTM D 445	cSt	11.1	14.8	14.6	19.8
Viscosity Index	ASTM D 2270	-	141	153	136	127
TBN	ASTM D 2896	mgKOH/g	7.2	7.2	7.2	7.2

Specifications, Approvals & Recommendations

- | | |
|---------|----------------------------|
| * API | SQ-RC IN SAE 10W30 & 10W40 |
| * API | SQ IN SAE 15W40 & 20W50 |
| * ILSAC | GF-7A IN SAE 10W30 |

Reference No.
5157G2SQREV0

Last revised date:
4/9/2025