

# UNITED ACTIVE MCO 2T

## Product Description

Hydrotreated 2T motorcycle oil formulated with high-quality hydrotreated base oils, this 2-stroke motorcycle oil helps to prevent spark plug fouling and ensures smoother engine operation. It keeps the engine system clean by minimizing carbon build-up and combustion residues. The formulation provides better protection against piston deposits, ring sticking, piston scuffing, and pre-ignition. Enhanced lubricity and thermal stability help protect engine components under high-temperature and high-load operating conditions, contributing to extended engine life and sustained performance.

## Applications / Benefits

- \* Avoid spark plug fouling
- \* Keep the engines clean
- \* Provide maximum protection against piston deposit, rig sticking, piston lightening and pre-ignition
- \* Mixing instruction for a pre-mix:  
Should mixed with gasoline at the ratio recommended by the engine manufacturer

## Typical Characteristics

| Test Description            | Method      | Unit |       |
|-----------------------------|-------------|------|-------|
| Density @ 15 °C             | ASTM D 4052 | kg/L | 0.862 |
| Flash Point                 | ASTM D 92   | °C   | 218   |
| Pour Point                  | ASTM D 97   | °C   | -12   |
| Kinematic Viscosity @ 40°C  | ASTM D 445  | cSt  | 52.4  |
| Kinematic Viscosity @ 100°C | ASTM D 445  | cSt  | 7.5   |
| Viscosity Index             | ASTM D 2270 | -    | 104   |