

UNITED MX 2T

Product Description

Two-Stroke oil formulated with premium quality lubricant to meet API TB requirement by providing engine cleanliness, reducing spark plug fouling, port blocking and scuff formation. It provides rust protection and enhances pre-ignition for optimum performance power. It is suitable for most popular types of air-cooled motorcycle engines particularly for the high performance motorcycle with oil injection systems.

This product is suitable to use with pre-mixed petrol-oil or separate oil injection systems. Therefore, it can be introduced directly into the petrol tank with no prior mixing required. The petrol to oil ratio should be in accordance with the engine manufacturer's recommendations.

Applications / Benefits

- * Good engine cleanliness & high resistance to deposit formation
- * Cleans and completely combustible
- * Good engine protection
- * Maximizes engine performance

Typical Characteristics

Test Description	Method	Unit	
Density @ 15 °C	ASTM D 4052	kg/L	0.868
Flash Point	ASTM D 92	°C	222
Pour Point	ASTM D 97	°C	-12
Kinematic Viscosity @ 40°C	ASTM D 445	cSt	54.5
Kinematic Viscosity @ 100°C	ASTM D 445	cSt	7.7
Viscosity Index	ASTM D 2270	-	104
Odor	-	-	Strawberry

Specifications, Approvals & Recommendations

* API TB

Reference No.
0711G2TBMX2TREVO

Last revised date:
23/6/2026