

UNITED MX 4T

Product Description

4 stroke motorcycle oil specially formulated with premium grade paraffinic mineral oil. This motorcycle oil viscosity is optimized to enhance its performance at high temperatures. With its natural high viscosity index, it gives better viscosity response towards temperature changes. Therefore, the engines can start much easier and oil can reach critical engine parts faster when the engine starts.

This motorcycles oil comes in SAE viscosity grades and can be used in small and light duty 4-stroke motorcycle engines.

Applications / Benefits

- * Promotes engine protection
- * Recommended for 4 stroke motorcycle engines
- * Naturally high viscosity index
- * Value-for-money product

Typical Characteristics

Test Description	Method	Unit		
SAE Viscosity Grade	SAE J 300	-	40	20W50
Density @ 15 °C	ASTM D 4052	kg/L	0.888	0.890
Flash Point	ASTM D 92	°C	235	238
Pour Point	ASTM D 97	°C	-9	-18
Kinematic Viscosity @ 40°C	ASTM D 445	cSt	143	176
Kinematic Viscosity @ 100°C	ASTM D 445	cSt	14.5	19.5
Viscosity Index	ASTM D 2270	-	100	127

Reference No.
BOG2MCO4TREV0

Last revised date:
23/1/2024