

UNITED MX SUPER 4T

Product Description

Hydrotreated four-stroke motorcycle engine oil formulated with high quality base oils to deliver dependable performance. It is specifically engineered to provide stable wear protection and consistent lubrication for conventional motorcycle engines requiring a reliable fluid.

This fluid ensures basic hardware reliability by maintaining the necessary oil film thickness under standard workloads. It also helps resist fluid degradation and thermal breakdown under normal operating conditions.

Applications / Benefits

- * Reduces engine wear and extends engine life
- * Protects engine under severe operating condition
- * Retards harmful deposit formation on vital engine parts
- * Protects against rust and corrosion

Typical Characteristics

Test Description	Method	Unit	
SAE Viscosity Grade	SAE J 300	-	15W40
Density @ 15 °C	ASTM D 4052	kg/L	0.869
Flash Point	ASTM D 92	°C	224
Pour Point	ASTM D 97	°C	-27
Kinematic Viscosity @ 40°C	ASTM D 445	cSt	109.4
Kinematic Viscosity @ 100°C	ASTM D 445	cSt	14.8
Viscosity Index	ASTM D 2270	-	140
TBN	ASTM D 2896	mgKOH/g	4.5

Suggested For The Following Uses

- | | |
|--------|-------|
| * API | SG/CF |
| * JASO | MA2 |

Reference No.
6128G2SGMA2REV0
CT0034

Last revised date:
2/7/2026