

UNITED MX ULTRA 4T API SL

Product Description

Synthetic motorcycle oil designed for four-stroke motorcycle engines. It contains a balanced blend of a specially selected synthetic base, high viscosity index base stocks and a special proprietary additive package. This motorcycle oil is engineered to provide unsurpassed wear protection, engine cleanliness and oxidation resistance, as well as consistent viscosity.

This product delivers the precise friction properties specifically required by the vehicles. It can be used in most 4T engines including Yamaha, Honda, Kawasaki, Suzuki, and Kubota.

Applications / Benefits

- * Reduces engine wear and extends engine life
- * Protects engine under severe operating conditions
- * Retards harmful deposit formation on vital engine parts
- * Protects against rust and corrosion

Typical Characteristics

Test Description	Method	Unit	5W40	5W50	10W30	10W40
SAE Viscosity Grade	SAE J 300	-	5W40	5W50	10W30	10W40
Density @ 15 °C	ASTM D 4052	kg/L	0.8619	0.8620	0.8576	0.8597
Flash Point	ASTM D 92	°C	220	222	216	218
Pour Point	ASTM D 97	°C	-36	-36	-30	-30
Kinematic Viscosity @ 40°C	ASTM D 445	cSt	87.7	115.9	75.2	98.3
Kinematic Viscosity @ 100°C	ASTM D 445	cSt	14.2	18.1	12.0	14.8
Viscosity Index	ASTM D 2270	-	168	174	155	156
TBN	ASTM D 2896	mgKOH/g	6.1	6.1	6.1	6.1

Typical Characteristics

Test Description	Method	Unit				
SAE Viscosity Grade	SAE J 300	-	15W40	15W50	20W40	20W50
Density @ 15 °C	ASTM D 4052	kg/L	0.8674	0.8702	0.8673	0.8705
Flash Point	ASTM D 92	°C	220	224	235	238
Pour Point	ASTM D 97	°C	-27	-27	-21	-21
Kinematic Viscosity @ 40°C	ASTM D 445	cSt	109.0	145.0	122.0	168.0
Kinematic Viscosity @ 100°C	ASTM D 445	cSt	15.0	18.9	15.6	19.7
Viscosity Index	ASTM D 2270	-	143	148	134	135
TBN	ASTM D 2896	mgKOH/g	6.1	6.1	6.1	6.1

Specifications, Approvals & Recommendations

* API	SL
* JASO	MA2

 Reference No.
 6128G23SLMA2REV0

 Last revised date:
 03-12-24