

UNITED MX ULTRA SCOOTER 4T

Product Description

Synthetic oil for motorcycles of which operating conditions are considerably different from passenger cars, resulting in increased specification complexity in the motorcycle oil market. This product is a tailored high-performance product to meet the unique demands of the 4 stroke motorcycle. It not only lubricates critical engine components, but also provides protection for clutch assemblies and gearboxes.

This product is formulated with the right combination and balance of component to combat undesirable potential issues such as gear pitting, clutch slip and higher levels of engine deposits. The advanced motorcycle oil is designed to deliver exceptional control from wear, corrosion and deposit formation as well as improved oxidative and thermal stability.

This product provides unsurpassed clutch performance and friction durability throughout the oil life, providing smoother operation and extended engine life with a consistent and enjoyable overall riding experience.

Applications / Benefits

- * Protects engine under severe operating conditions
- * Enhanced piston and engine cleanliness
- * Retards harmful deposit formation on vital engine parts
- * Provide clutch friction durability

Typical Characteristics

Test Description	Method	Unit	
SAE Viscosity Grade	SAE J 300	-	10W40
Density @ 15 °C	ASTM D 4052	kg/L	0.964
Flash Point	ASTM D 92	°C	220
Pour Point	ASTM D 97	°C	-33
Kinematic Viscosity @ 40°C	ASTM D 445	cSt	97.33
Kinematic Viscosity @ 100°C	ASTM D 445	cSt	14.77
Viscosity Index	ASTM D 2270	-	158

Specifications, Approvals & Recommendations

	10W40
* API	SP
* JASO	MB

Reference No.
6120G23SPMB4TREVO

Last revised date:
7/3/2024