

UNITED RACE

Product Description

Hydrotreated Passenger Car Motor Oil is formulated with high-quality Group II base oils and a balanced additive system to provide dependable lubrication for gasoline-powered passenger vehicles operating under a wide range of driving conditions. The formulation supports engine cleanliness and helps maintain stable oxidation performance, while contributing to protection against wear and deposit formation commonly encountered in modern engine operation.

The oil is designed to maintain consistent viscosity characteristics across varying operating temperatures and loads, supporting reliable lubrication of critical engine components. It also assists in controlling sludge and deposit formation, helping to maintain engine cleanliness and support smooth engine operation and durability during normal service conditions.

Applications / Benefits

- * Reliable engine wear protection
- * Helps control sludge and deposits
- * Stable viscosity at high temperatures
- * Supports long engine life

Typical Characteristics

Test Description	Method	Unit	
SAE Viscosity Grade	SAE J 300	-	25W50
Density @ 15 °C	ASTM D 4052	kg/L	0.888
Flash Point	ASTM D 92	°C	248
Pour Point	ASTM D 97	°C	-15
Kinematic Viscosity @ 40°C	ASTM D 445	cSt	200.8
Kinematic Viscosity @ 100°C	ASTM D 445	cSt	20.8
Viscosity Index	ASTM D 2270	-	122

Suggested For The Following Uses

- | | |
|--------|-------|
| * API | SL |
| * ACEA | A3/B4 |

Reference No.
5182G2SLA3B4RACEREVO

Last revised date:
6/3/2026